

NEC

	Diagonale	Bezeichnung	Auflösung	Farben	Maße (mm)	Helligkeit (cd/m²)	Kontrast	Blickwinkel (O / U / L / R)	Betriebs-temp. (°C)	Schnittstelle	Special Features
LED!	3,5"	NL2432HC22-40J	240 x 320	262K	63,5 x 85 x 3	220/15%	150:1	35°/35°/35°/35°	-20 - +70	CMOS	transflective, (SR-NLT), LED
LED!	3,5"	NL2432HC22-41K	240 x 320	262K	63,5 x 85 x 4,2	200/15%	150:1	30°/35°/30°/30°	-20 - +70	CMOS	transflective (SR-NLT), LED, Touch
	5,5"	NL3224AC35-01	320 x 240	Full	134 x 110 x 23	250	85:1	30°/15°/45°/45°	-30 - +85	analog, NTSC/PAL	wide temperature range, not for new design
	5,5"	NL3224BC35-20	320 x 240	262K	134 x 104,5 x 12,5	400	400:1	40°/50°/55°/55°	-10 - +70	CMOS	QVGA
	5,5"	NL3224BC35-22	320 x 240	262K	134 x 104,5 x 12,5	29%/750	500:1	40°/50°/55°/55°	-10 - +70	CMOS	QVGA, NLT
LED New!	5,7"	NL6448BC18-01	640 x 480	262K	135 x 104,6 x 10,5	400	1000:1	80°/80°/80°/80°	-20 - +70	CMOS	VGA, LED backlight
LED New!	5,7"	NL6448BC18-01F	640 x 480	262K	135 x 104,6 x 10,5	800	1000:1	80°/80°/80°/80°	-20 - +70	CMOS	VGA, LED backlight
	6,3"	NL10276BC12-02	1027 x 768	16,7 Mio	178,8 x 126,8 x 12	250	500:1	45°/60°/60°/60°	0 - +65	LVDS, 1 ch, 6/8 bit	XGA, not for new design
LED New!	6,5"	NL10276BC13-01	1024 x 768	262K/16,7 Mio	153 x 118 x 9,5	500	500:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	XGA, LED backlight
LED!	6,5"	NL10276BC13-01C	1024 x 768	262K/16,7 Mio	153 x 118 x 9,5	600	500:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	XGA, NLT, LED backlight
	6,5"	NL6448BC20-08E	640 x 480	262K	178,8 x 126,8 x 11,5	300	250:1	35°/45°/50°/50°	0 - +60	CMOS	not for new design
	6,5"	NL6448BC20-18D	640 x 480	262K	153 x 118 x 10,5	400	600:1	80°/60°/80°/80°	-10 - +70	CMOS	XGA, side mount
	6,5"	NL6448BC20-20	640 x 480	262K	153 x 118 x 10,5	650	600:1	80°/60°/80°/80°	-10 - +70	CMOS	XGA, NLT, side mount
LED New!	6,5"	NL6448BC20-21C	640 x 480	262K/16,7 Mio	153 x 118 x 9,5	800	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	XGA, NLT, side mount, LED backlight
LED New!	6,5"	NL6448BC20-21D	640 x 480	262K/16,7 Mio	153 x 118 x 9,5	550	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	XGA, side mount, LED backlight
LED New!	7"	NL8048BC19-02	800 x 480	262k/16,7 Mio	170 x 111 x 8,5	400	1000:1	80°/80°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	wide VGA, LED backlight
LED New!	7"	NL8048BC19-02C	800 x 480	262k/16,7 Mio	170 x 111 x 8,5	550	900:1	80°/80°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	wide VGA, NLT, LED-Backlight
LED New!	7"	NL8048BC19-03	800 x 480	262K/16,7 Mio	170 x 91,44 x 8,5	400	1000:1	80°/80°/80°/80°	-20 - +40	LVDS, 1 ch, 6/8 bit	wide VGA, Portrait format, LED backlight
	7"	NL4823BC37-05	480 x 234	262K	174,5 x 105,5 x 10,5	400	600:1	60°/80°/80°/80°	-20 - +70	CMOS	wide QVGA
	8,4"	NL6448BC26-01	640 x 480	262K	200 x 152 x 12	450	500:1	40°/70°/55°/55°	0 - +65	CMOS	VGA
	8,4"	NL6448BC26-08D	640 x 480	262K/16,7 Mio	200 x 152 x 10,5	400	800:1	85°/85°/85°/85°	-10 - +70	LVDS, 1 ch, 6/8 bit	VGA, UA-SFT
	8,4"	NL6448BC26-09	640 x 480	262k	200 x 152 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	CMOS	UA
	8,4"	NL6448BC26-09C	640 x 480	262k	200 x 152 x 10,5	750	600:1	80°/60°/80°/80°	-20 - +70	CMOS	VGA, NLT
	8,4"	NL6448BC26-15	640 x 480	262K/16,7 Mio	200 x 152 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	VGA
LED New!	8,4"	NL6448BC26-22F	640 x 480	262K	200 x 152 x 10,5	800	1000:1	80°/80°/80°/80°	-20 - +70	CMOS	High Brightness, VGA, LED backlight
	8,4"	NL8060BC21-02	800 x 600	262K/16,7 Mio	200 x 152 x 10,5	400	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA
	8,4"	NL8060BC21-03	800 x 600	262K/16,7 Mio	200 x 152 x 10,5	650	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA, NLT
	8,4"	NL8060BC21-04	800 x 600	262K	200 x 152 x 10,5	400	600:1	80°/60°/80°/80°	-20 - +70	CMOS	SVGA
New!	8,4"	NL8060BC21-06	800 x 600	262k/16,7 Mio	200 x 152 x 10,5	650	600:1	60°/80°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA
	8,4"	NL10276BC16-01	1024 x 768	262K/16,7 Mio	200 x 152 x 16,5	400	400:1	85°/85°/85°/85°	0 - +65	LVDS, 1 ch, 6/8 bit	XGA, UA-SFT, 72% NTSC
LED New!	8,9"	NL10260BC19-01D	1024 x 600	262K/16,7 Mio	214 x 129 x 5,7	300	500:1	88°/88°/88°/88°	-20 - +70	LVDS, 1 ch, 6/8 bit	wide SVGA, LED backlight, UA-SFT
	9"	NL8048BC24-01	800 x 480	262K/16,7 Mio	220,5 x 136,5 x 10,5	400	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	wide VGA
New!	9"	NL8048BC24-04	800 x 480	262K/16,7 Mio	220,5 x 136,5 x 10,5	350	700:1	88°/88°/88°/88°	-20 - +70	LVDS, 1 ch, 6/8 bit	wide VGA, UA-SFT (based on NL8048BC24-01)
	10,4"	NL6448BC33-50	640 x 480	262K	243 x 185,1 x 10,5	250/5%	100:1	40°/55°/75°/55°	0 - +70	CMOS	VGA, transflective (SR-NLT)
	10,4"	NL6448BC33-53	640 x 480	262K	243 x 185,1 x 10,5	380	500:1	85°/85°/85°/85°	-10 - +70	CMOS	VGA, SA-SFT
	10,4"	NL6448BC33-54	640 x 480	262K	243 x 185,1 x 10,5	220	350:1	30°/20°/45°/45°	-10 - +70	CMOS	VGA, standard 10.4 model
	10,4"	NL6448BC33-59	640 x 480	262K	243 x 185,1 x 10,5	450	600:1	45°/55°/70°/70°	-10 - +70	CMOS	VGA, not for new design
	10,4"	NL6448BC33-63C	640 x 480	262K/16,7Mio	243 x 185,1 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	VGA, NLT
	10,4"	NL6448BC33-63D	640 x 480	262K/16,7Mio	243 x 185,1 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	VGA
	10,4"	NL6448BC33-64	640 x 480	262K	243 x 185,1 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	CMOS	VGA
	10,4"	NL6448BC33-64C	640 x 480	262K	243 x 185,1 x 10,5	450	600:1	80°/60°/80°/80°	-20 - +70	CMOS	VGA, NLT
New!	10,4"	NL6448BC33-74	640 x 480	262K	243 x 185,1 x 10,5	450	800:1	88°/88°/88°/88°	-20 - +70	CMOS	UA-SFT, successor model of NL6448BC33-53
	10,4"	NL8060BC26-27	800 x 600	262K	243 x 185,1 x 10,5	400	700:1	85°/85°/85°/85°	-10 - +70	CMOS	SA-SFT
	10,4"	NL8060BC26-28	800 x 600	262K/16,7 Mio	243 x 185,1 x 10,5	400	700:1	85°/85°/85°/85°	-10 - +70	LVDS, 1 ch, 6/8 bit	SA-SFT
	10,4"	NL8060BC26-30C	800 x 600	262K/16,7 Mio	243 x 185,1 x 10,5	500	900:1	80°/80°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA, TN, NLT
New!	10,4"	NL8060BC26-30D	800 x 600	262K/16,7 Mio	243 x 185,1 x 10,5	400	1000:1	80°/80°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	TN, LVDS
New!	10,4"	NL10276BC20-04	1024 x 768	262K	243 x 185,1 x 11	300	300:1	45°/60°/60°/60°	0 - +60	LVDS, 1 ch, 6 bit	XGA, TN
	10,4"	NL10276BC20-04C	1024 x 768	262K	243 x 185,1 x 11	300	300:1	45°/60°/60°/60°	0 - +60	LVDS, 1 ch, 6 bit	XGA, TN, NLT
	10,4"	NL10276BC20-08	1024 x 768	262K	227 x 174,5 x 10,5	300	700:1	85°/85°/85°/85°	0 - +65	LVDS, 1 ch, 6 bit	XGA, SA-SFT, small outline
	12,1"	NL8060BC31-20	800 x 600	262K	280 x 210 x 13	250	400:1	80°/80°/80°/80°	0 - +55	CMOS	SVGA, A-SFT
	12,1"	NL8060BC31-27	800 x 600	262K	280 x 210 x 13	400	600:1	45°/55°/70°/70°	-10 - +70	CMOS	SVGA, TN, not for new design
	12,1"	NL8060BC31-32	800 x 600	262K	280 x 210 x 13	400	600:1	45°/55°/70°/70°	-10 - +70	CMOS	SVGA, NLT
	12,1"	NL8060BC31-36	800 x 600	262K	280 x 209 x 16,5	1100	600:1	45°/55°/70°/70°	-10 - +70	CMOS	SVGA, TN, ultra high luminance
	12,1"	NL8060BC31-28D	800 x 600	262K	280 x 210 x 13	350	600:1	45°/55°/70°/70°	-10 - +70	LVDS, 1 ch, 6 bit	SVGA, TN
New!	12,1"	NL8060BC31-41C	800 x 600	262K/16,7 Mio	280 x 210 x 11	550	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA, NLT-Version vom BC31-41D
	12,1"	NL8060BC31-41D	800 x 600	262K/16,7 Mio	280 x 210 x 11	400	600:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 6/8 bit	SVGA, TN
	12,1"	NL8060BC31-42	800 x 600	262K	280 x 210 x 11	400	600:1	80°/60°/80°/80°	-20 - +70	CMOS	SVGA, clear surface
	12,1"	NL8060BC31-42D	800 x 600	262K	280 x 210 x 11	400	600:1	80°/60°/80°/80°	-20 - +70	CMOS	SVGA, antiglare surface
	12,1"	NL10276BC24-13	1024 x 768	262K/16,7 Mio	280 x 210 x 13	400	600:1	45°/55°/70°/70°	-10 - +70	LVDS, 1 ch, 6/8 bit	XGA
	12,1"	NL10276BC24-13C	1024 x 768	262K/16,7 Mio	280 x 210 x 13	400	600:1	45°/55°/70°/70°	10 - +70	LVDS, 1 ch, 6/8 bit	XGA, NLT
LED New!	12,1"	NL10276BC24-19D	1024 x 768	262K	260,0 x 200 x 6,9	650	600:1	60°/60°/70°/70°	-20 - +60	LVDS, 1 ch, 6 bit	XGA, LED-Backlight, nur 6,9 mm dick!
	15"	NL10276BC30-15	1024 x 768	16,7 Mio	328 x 252 x 11	250	400:1	40°/60°/60°/60°	0 - +55	LVDS, 1 ch, 8 bit	XGA, PSWG
	15"	NL10276BC30-17	1024 x 768	16,7 Mio	326,5 x 253,5 x 17	350	700:1	85°/85°/85°/85°	0 - +55	LVDS, 1 ch, 8 bit	XGA, UA-SFT, PSWG
	15"	NL10276BC30-18	1024 x 768	16,7 Mio	326,5 x 253,5 x 17	500	500:1	80°/60°/80°/80°	-10 - +70	LVDS, 1 ch, 8 bit	High brightness, wide temperature range, PSWG
	15"	NL10276BC30-18C	1024 x 768	16,7 Mio	326,5 x 253,5 x 17	600	600:1	80°/60°/80°/80°	-10 - +70	LVDS, 1 ch, 8 bit	NLT, wide temperature range, PSWG
	15"	NL10276BC30-32D	1024 x 768	16,7 Mio	326,5 x 253,5 x 12	250	500:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 8 bit	XGA, PSWG, low cost
	15"	NL10276BC30-33D	1024 x 768	16,7 Mio	326,5 x 253,5 x 12	400	500:1	80°/60°/80°/80°	-20 - +70	LVDS, 1 ch, 8 bit	XGA, PSWG
	15,3"	NL12876BC26-25	1280 x 768	16,7 Mio	358 x 226 x 15,8	470	700:1	85°/85°/85°/85°	-10 - +70	LVDS, 1 ch, 8 bit	wide-XGA, SA-SFT
	18,1"	NL128102AC28-07	1280 x 1024	16,7 Mio	389 x 317,2 x 30,3	240	300:1	85°/85°/85°/85°	0 - +66	LVDS, 2 ch, 8 bit	SXGA, not for new design
	19"	NL128102BC29-01B	1280 x 1024	16,7 Mio	404,2 x 330 x 22	280	450:1	85°/85°/85°/85°	0 - +55	LVDS, 2 ch, 8 bit	wide color gamut, SA-SFT, high uniformity
New!	19"	NL128102BC29-10	1280 x 1024	16,7 Mio	404,2 x 330 x 22	300	800:1	88°/88°/88°/88°	0 - 60	LVDS, 2-ch, 8 bit	UA-SFT, wide color gamut, high uniformity
	20,1"	NL128102AC31-02	1280 x 1024	16,7 Mio	470 x 382 x 42,5	250	300:1	85°/85°/85°/85°	0 - +55	LVDS, 2 ch, 8 bit	
	21,3"	NL160120AC27-05	1600 x 1200	16,7 Mio	457 x 350 x 34	450					